



Petrolatum Anti-Corrosion Tapes

Petrolatum Anti-Corrosion Tape is a non-hardening and non-cracking corrosion protection wrap .Petrolatum Tape for Pipe Corrosion Protection is also called wax tape, grease tape. It is highly resistant to mineral acids, alkalis, salts and micro-organisms and highly impermeable to water vapor and gases. Used for the protection of buried or exposed pipes, rods, cable, valves and metal fittings from corrosion.

It is composed of a non woven fibre fabric coated with a neutral compound based on saturated petrolatum and inert siliceous fillers.

STRUCTURE

Non-woven synthetic fibre impregnated and coated with a neutral compound based on saturated petrolatum hydrocarbons (Petrolatum) and inert siliceous fillers. It is supplied in rolls in a range of widths.

Office: +86(574)8388 2233

Dongxi, Xinqiao, Xiangshan
Ningbo 315725, P.R.China

info@yuxi-anode.com

www.yuxi-anode.com

FEATURES

- ▶ Suitable to irregular shapes and profiles
- ▶ It can be applied to cold ,wet surfaces.
- ▶ It can be applied above and below ground.
- ▶ Excellent resistance water, acid, salts or soil organics

ORDERING INFORMATION

YUXI petrolatum tapes are available in rolls.

Product Type	Standard Ordering Options
Tape Thickness	1.2mm
Tape Width	50mm、 100mm、 150mm、 200mm
Tape Length	10m
Tape Color	Brown、 Yellow
Core Diameter	38mm or others

SPECIFICATIONS

property	Test Method	Typical Value
Tensile Strength	ASTM D1000	> 40N/cm
Elongation	ASTM D1000	15%
Breakdown Voltage(55% overlap)		> 18KV
Chemical Resistance (7days ,10% Hydrochloric Acid)		Excellent
Chemical Resistance (7days ,20% Sodium Chloride)		Excellent
Chemical Resistance (7days ,10% Potassium Chloride)		Excellent
Color		Brown、 Light Yellow
Thickness	ASTM D1000	1.2mm
Width	ASTM D1000	50mm, 100mm, 150mm
Length	ASTM D1000	10m
Weight		1.5kg/m ²
Temperature Range Application Service		-30℃ - 70℃ -5℃ - 45℃